

MIG/MAG-KAUKOSÄÄTIMET



TR 1000



TR 1100



TR 1200



TR 1300



TR 1600



TR 2000



TR 2100



TR 2200 F



TR 2200-FM



TR 3000



TR 4000



TR 4000 C



RCU 4000



RCU 5000i

	4,046,082 - Display remote control TR1000 with cable 5m	4,046,085 - Remote control TR 1100 with cable 4,5m	4,046,092 - Remote control TR 1200 Universal with cable 5m	4,046,093 - Remote control TR 1300 Universal with cable 5m	4,046,095 - Remote control TR 1600 Universal with cable 5m	4,046,079 - Remote control TR 2000 with cable 5m	4,046,091 - Remote control TR2100 TIME with cable 5m	4,046,090 - Remote control pedal operated TR 2200-F with cable 5m	4,046,090,630 - Remote control pedal operated TR 2200-FM Universal with cable 5m	4,046,083 - Remote control electrode TR 3000 with cable 5m	4,046,080 - Universal operation TR 4000 with cable 5m	4,046,081 - Extra-convenient TR4000 C operated with cable/5m	4,045,859 - RCU4000 remote control	4,045,859,800 - RCU 4000 remote control	4,046,098 - Remote control RCU 5000i Universal SD
Options															
4,100,265 - I-kit magnet for RC							•	•				•	•		
4,100,433 - I-kit mounting RCU5000i															•
Adjustable parameter															
Welding current	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S
MMA arc force						S				S		S	S	S	S
Hotstart											S	S	S	S	S
Welding power											S	S	S	S	S
Wire feed speed	S	S				S	S				S	S	S	S	S
Welding voltage arc length	S	S				S	S				S	S	S	S	S
Globule shedding											S	S	S	S	S
MIG arc force											S	S	S	S	S
Puls / Standard												S	S	S	S
Puls / Standard / Manual												S	S	S	S
Job recall	S	S										S	S	S	S
Job creation												S	S	S	S